

ASC系列流量控制阀

ASC Series Flow Control Valve



ASC-06



ASC-08

订购码 Ordering Code

ASC
08
系列代号
Series Code

接管口径
Port Size

ASC: 单向流阀

ASC: One-way throttle valve

06:G1/4" 25:G1"


08:G1/4" 32:G1-1/4"

10:G3/8" 40:G1-1/2"

15:G1/2" 40:G1-1/2"

20:G3/4"

符号 Symbol




规格 Specification


型号 Mode	ASC-06	ASC-08	ASC-10	ASC-15
工作介质 Working medium	空气 Air			
接管口径 Port size	G1/8"	G1/4"	G3/8"	G1/2"
使用压力范围 The use of pressure	0.5~9.5Kg/cm ²			
保证耐压力 Max. proof pressure	15.0Kg/cm ²			
使用温度范围 Working temperature	-0.5~60℃			
本体材质 Material	铝合金 Aluminum alloy 6061-T6		铝合金 Aluminum alloy ADC-16	
标准额定流量 Standard rated flow	200		1250	1650
	400		1500	2500

外形尺寸图 Overall Dimension Drawing(mm)


ASC-06





ASC-08



ASC-10



ASC-15



符号/型号 Model/ Symbol	A	B	C	D	E	F	G	H	I	J	K	L	M	N
ASC-06	22	32	G1/8"	18	23	4.3	46.8	52.3	M6×0.5	M12×1	10	18	26	8.6
ASC-08	26	36	G1/4"	23	27	4.3	50.8	56.3	M6×0.5	M12×1	13.5	18	30	8.6
ASC-10	35	50	G3/8"	32	37	5.3	65	74	M8×0.75	M16×1.0	17.5	28	40.5	10.2
ASC-15	35	50	G1/2"	32	37	5.3	60	74	M8×0.75	M16×1.0	17.5	28	40.5	10.2