

2YV系列二位二通电磁阀


2V Series Two-position Two-way Solenoid Valve



订购码 Ordering Code

2YV	025	06	AC220V
规格代码 Specification Code	流量孔径 Aperture of Flow Rate	接管口径 Piping Size	标准电压 Standard voltage
2YV:二位二通电磁阀 2V:Two-position Two-way	020: 2mm 025: 2.5mm	06: G1/8 08: G1/4	DC12V DC24V AC24V 50Hz/60Hz AC110V 50Hz/60Hz AC220V 50Hz/60Hz AC380V 50Hz/60Hz

符号 Symbol



规格 Specification

型号 Model	2V025-06	2V025-08
工作介质 Working medium	空气、水、油/Air,Water,Oil	
动作方式 Action mode	直动式/Direct Drive	
型式 Type	常闭型/Normal Close Type	
流量孔径 mm Aperture of Flow Rate	2.5	
CV值 CV Value	0.23	
接管口径 Joint pipe Bore	G1/8	G1/4
使用流体粘滞度 Operation Fluid Viscosity	20 CST以下(Below)	
使用压力 Mpa Working-pressure	空气、水、油/Air,Water,Oil:0.~1.0MPa	
最大耐压力 Max. pressure Resistance	1.5MPa	
工作温度℃ Operating Temperature	-10~80℃	
使用电压范围 Voltage Range	± 10%	
保护等级 Protect Class	IP65	
耗电量 Power consumption	AC: 4.5VA DC:3W	
绝缘性 Insulation	F级 / F Class	
本体材质 Body Material	铝或铜/Aluminum or Brass	
油封材质 Material of Oil Seal	NBR或VITON	
最短励磁时间 Shortest excitation time	0.05秒	

外形尺寸图 Overall Dimension Drawing(mm)

